





Material Safety Data Sheet

NFPA	WHMIS	PPE	Transport Symbol
	Non-controlled		Not regulated

Revision Date: 06-Oct-2009

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Pro Honda GN4 MC Oil SAE 10W-40 SJ, 12 x 1 Quart Case
Product Code: 2208-042
Recommended use: 4 Stroke Motorcycle Engine Oil

Contact Manufacturer
Idemitsu Lubricants America,
701 Port Rd.
Jeffersonville, IN. 47130
Telephone: 812-285-8234
Fax: 812-285-8243
Contact Name: Robin Hutchens
Email: rhutchens@ilacorp.com

Emergency Telephone Number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

CAUTION!

Emergency Overview

vapors may be irritating to eyes, nose, throat, and lungs

Appearance Brown Oily Liquid

Physical State: Liquid

Odor: Mild

Mexico - Grade Slight risk, Grade 1

Potential Health Effects

Principle Routes of Exposure Skin, Eye

Acute Effects

Eyes

May cause slight irritation

Skin

Substance may cause slight skin irritation

Inhalation

May cause irritation of respiratory tract

Ingestion

May be harmful if swallowed

Chronic Effects

Prolonged exposure may cause chronic effects.

See Section 11 for additional Toxicological information.

Signs and Symptoms: Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract

Potential Environmental Effects See Section 12 for additional Ecological information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.

Non-Hazardous Components

Chemical Name	CAS-No	Weight %
Lubricating Base Stocks	Mixture	>80

4. FIRST AID MEASURES

General Advice	Take off contaminated clothing and shoes immediately. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. If symptoms persist, call a physician.
Ingestion	Do not induce vomiting without medical advice. Call a physician or Poison Control Center immediately.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing.

5. FIRE-FIGHTING MEASURES

Flammable Properties	NFPA: Class IIIB Combustible Liquid
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Hazardous combustion products	Carbon oxides. nitrogen oxides (NOx). oxides of phosphorus.
Specific Hazards Arising from the Chemical	
Keep product and empty container away from heat and sources of ignition	

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

NFPA Health: 0 Flammability: 1 Instability: 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Avoid contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition. Avoid breathing vapors or mists. Ensure adequate ventilation.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Prevent product from entering drains. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

Methods for Clean-up

Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Pick up and transfer to properly labeled containers.

Spill Management

LARGE SPILLS

Eliminate sources of ignition. Prevent additional discharge of material if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify the National Response Center.

WATER SPILLS

Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations

7. HANDLING AND STORAGE

Handling

Wear personal protective equipment. Do not breathe vapors or spray mist. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place

Safe Handling Advice

Handle in accordance with good industrial hygiene and safety practices

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	ILA IHG	ILA ROEG
Oil mist, mineral	TWA: 5 mg/m ³	TWA: 5 mg/m ³ STEL: 10 mg/m ³	10 mg/m ³		

Engineering measures	Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed above is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.
Personal Protective Equipment	
Eye/face Protection	Safety glasses with side-shields
Skin Protection	Wear protective gloves/clothing. Glove Type: Neoprene, Nitriles
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations
General Hygiene Considerations	When using, do not eat, drink or smoke. Clean equipment, work area and clothing regularly.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Brown Oily Liquid
Odor:	Mild
Physical State:	Liquid
Flash Point	226°C / 439°F
Method	COC ASTM D92
Density	0.87 g/cm ³ @15°C
Viscosity	@40C = 92.53 cSt; @100C = 13.64 cSt

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended storage conditions. Hazardous polymerization does not occur.
Conditions to Avoid	Heat, flames and sparks
Incompatible Materials	Strong oxidizing agents.
Hazardous decomposition products	Thermal decomposition can lead to release of irritating gases and vapors

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information (Estimated):

LD50 Oral:	4139.18 mg/kg
LD50 Dermal:	2226.39 mg/kg

Chronic Toxicity

Carcinogenicity:

There are no known carcinogenic chemicals in this product.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Lubricant oil basestocks are complex mixtures of hydrocarbons (primarily branched chain alkanes and cycloalkanes) ranging in carbon number from C15 to C50. The aromatic hydrocarbon content of these mixtures varies with the severity of the refining process. White oils have negligible levels of aromatic hydrocarbons, whereas significant proportions are found in unrefined basestocks. Olefins are found only at very low concentrations. Volatilization is not significant after release of lubricating oil basestocks to the environment due to the very low vapor pressure of the hydrocarbon constituents. In water, lubricating oil basestocks will float and will spread at a rate that is viscosity dependent. Water solubilities are very low and dispersion occurs mainly from water movement with adsorption by sediment being the major fate process. In soil, lubricating oil basestocks show little mobility and adsorption is the predominant physical process.

Both acute and chronic ecotoxicity studies have been conducted on lubricant base oils. Results indicate that the acute aquatic toxicities to fish, Daphnia, Ceriodaphnia and algal species are above 1000 mg/l using either water accommodated fractions or oil in water dispersions. Since lubricant base oils mainly contain hydrocarbons having carbon numbers in the range C15 to C50, it is predicted that acute toxicity would not be observed with these substances due to low water solubility. Results from chronic toxicity tests show that the no observed effect level (NOEL) usually exceeds 1000 mg/l for lubricant base oils with the overall weight of experimental evidence leading to the conclusion that lubricant base oils do not cause chronic toxicity to fish and invertebrates.

Large volumes spills of lubricant base oils into water will produce a layer of undissolved oil on the water surface that will cause direct physical fouling of organisms and may interfere with surface air exchange resulting in lower levels of dissolved oxygen. Petroleum products have also been associated with causing taint in fish even when the latter are caught in lightly contaminated environments. Highly refined base oils sprayed onto the surface of eggs will result in a failure to hatch.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of in accordance with local regulations

14. TRANSPORT INFORMATION

DOT

Not regulated

IATA

Not regulated

IMDG/IMO

Not regulated

15. REGULATORY INFORMATION

International Inventories

All components in the product are on the following Inventory Lists: U.S.A. (TSCA), Canada (DSL/NDSL), Korea (ECL), China (IECSC), Philippines (PICCS).

USA

Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any HAPs.

State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

State Right-to-Know

This product does not contain any substances regulated by state right-to-know regulations.

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

Non-controlled

16. OTHER INFORMATION

Revision Date: 06-Oct-2009

Revision Summary: Not available

Disclaimer:

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS